

# Safety Data Sheet

## Butonal® NX 4190

Revision date : 2022/04/07

Version: 5.0

Page: 1/10

(30508809/SDS\_GEN\_MX/EN)

### 1. Identification

#### Product identifier used on the label

## Butonal® NX 4190

#### Recommended use of the chemical and restriction on use

Recommended use\*: for industrial use only

Recommended use\*: Raw material

Unsuitable for use: Uses other than recommended

Suitable for use in industrial sector: chemical industry

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF Mexicana S.A. de C.V.

Av. Insurgentes Sur 975

Col. CD. De Los Deportes,

C.P. 03710 Ciudad de México

MÉXICO

Telephone: +52 55 5325 2600

#### Emergency telephone number

##### 24 Hour Emergency Response Information

SETIQ: 1800-00-214-(Rep. Mexicana) or 55-59-15-88 (CDMX)

Telephone: +1-800-849-5204 or +1-833-229-1000

#### Other means of identification

Chemical family: Polymer, dispersion

---

### 2. Hazards Identification

#### According to Regulation NOM-018-STPS-2015

#### Classification of the product

Eye Dam./Irrit.

2A

Serious eye damage/eye irritation

Aquatic Acute

2

Hazardous to the aquatic environment - acute

# Safety Data Sheet

## Butonal® NX 4190

Revision date : 2022/04/07  
Version: 5.0

Page: 2/10  
(30508809/SDS\_GEN\_MX/EN)

Aquatic Chronic Repr.	3	Hazardous to the aquatic environment - chronic
Repr.	1B (fertility)	Reproductive toxicity
Repr.	1B (unborn child)	Reproductive toxicity

### Label elements

Pictogram:



Signal Word:  
Danger

Hazard Statement:

H319	Causes serious eye irritation.
H360	May damage fertility. May damage the unborn child.
H412	Harmful to aquatic life with long lasting effects.
H401	Toxic to aquatic life.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P280	Wear eye protection.
P273	Avoid release to the environment.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P264	Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical attention.
P337 + P313	If eye irritation persists: Get medical attention.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.
------	---

### Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered. If the product adheres to skin, irritation may occur when it dries.

---

## 3. Composition / Information on Ingredients

### According to Regulation NOM-018-STPS-2015

Guanidine, N,N'-diphenyl-  
CAS Number: 102-06-7  
Content (W/W): > 0.0 - < 0.3%  
Synonym: 1,3-Diphenylguanidine; N,N'-Diphenylguanidine

# Safety Data Sheet

## Butonal® NX 4190

Revision date : 2022/04/07

Version: 5.0

Page: 3/10

(30508809/SDS\_GEN\_MX/EN)

### Ethanol

CAS Number: 64-17-5

Content (W/W):  $\geq 0.0$  -  $\leq 2.0\%$

Synonym: Ethyl alcohol

### Inorganic Substance

CAS Number: Trade Secret

Content (W/W):  $> 0.0$  -  $< 7.0\%$

Synonym: No data available.

### Quaternary ammonium compound

CAS Number: Trade Secret

Content (W/W):  $> 0.0$  -  $< 5.0\%$

Synonym: No data available.

### hydrochloric acid

CAS Number: 7647-01-0

Content (W/W):  $\geq 0.1$  -  $< 0.3\%$

Synonym: No data available.

### Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-Alcohols, C11-14-iso-, C13-rich, ethoxylated

CAS Number: 78330-21-9

Content (W/W):  $> 0.0$  -  $< 3.0\%$

Synonym: No data available.

---

## 4. First-Aid Measures

### Description of first aid measures

#### General advice:

Remove contaminated clothing.

#### If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

#### If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

#### If in eyes:

Flush with copious amounts of water for at least 15 minutes. If irritation develops, seek medical attention.

#### If swallowed:

Immediately rinse mouth and then drink 200 - 300 ml water, do not induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

### Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

# Safety Data Sheet

## Butonal® NX 4190

Revision date : 2022/04/07  
Version: 5.0

Page: 4/10  
(30508809/SDS\_GEN\_MX/EN)

*Information on: Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-Alcohols, C11-14-iso-, C13-rich, ethoxylated*

*Symptoms: Eye irritation, nausea, diarrhea, vomiting, choking, coughing, itching, skin irritation*

*Information on: hydrochloric acid*

*Symptoms: Overexposure may cause:, choking, dyspnea, coughing*

*Information on: Quaternary ammonium compound*

*Symptoms: Overexposure may cause:, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps*

*Information on: Inorganic Substance*

*Symptoms: Overexposure may cause:, convulsions, acidosis, pneumonia, lethargy, confusion, dyspnea, coughing, dizziness, lacrimation*

*Information on: Guanidine, N,N'-diphenyl-*

*Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.*

-----

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Symptomatic treatment (decontamination, vital functions).

---

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
water spray, foam, dry powder

Unsuitable extinguishing media for safety reasons:  
No data available.

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
No particular hazards known.

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered.

---

## 6. Accidental release measures

### Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

# Safety Data Sheet

## Butonal® NX 4190

Revision date : 2022/04/07  
Version: 5.0

Page: 5/10  
(30508809/SDS\_GEN\_MX/EN)

### Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Avoid contact with skin and eyes.

### Environmental precautions

Do not release untreated into natural waters.

### Methods and material for containment and cleaning up

For small amounts: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr). Dispose of absorbed material in accordance with regulations.

For large amounts: Pump off product.

Spills should be contained, solidified, and placed in suitable containers for disposal.

---

## 7. Handling and Storage

### Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. No special measures necessary provided product is used correctly. Ensure adequate ventilation.

### Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Store protected against freezing.

Protect from temperatures below: 5 °C

The packed product is destroyed at low temperatures or by frost.

Protect from temperatures above: 60 °C

The packed product must be protected against exceeding the indicated temperature.

---

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

Ethanol OEL, MX: STEL value 1,000 ppm ;

### Advice on system design:

Ensure adequate ventilation.

### Personal protective equipment

#### Respiratory protection:

Wear respiratory protection if ventilation is inadequate.

#### Hand protection:

Chemical resistant protective gloves

#### Eye protection:

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

#### General safety and hygiene measures:

Hands and/or face should be washed before breaks and at the end of the shift. Avoid contact with skin and eyes.

---

# Safety Data Sheet

## Butonal® NX 4190

Revision date : 2022/04/07

Version: 5.0

Page: 6/10

(30508809/SDS\_GEN\_MX/EN)

### 9. Physical and Chemical Properties

Form:	liquid, dispersion	
Odour:	aromatic	
Odour threshold:	No data available.	
Colour:	white	
pH value:	5.0 - 5.6	
Freezing point:	No data available.	
<i>Information on: Water</i>		
Melting point:	0 °C	
-----		
<i>Information on: Water</i>		
Boiling point:	100 °C	
-----		
Flash point:	> 300 °F	(Unspecified)
Flammability:	not flammable	
Lower explosion limit:	not applicable	
Upper explosion limit:	not applicable	
Autoignition:	Based on the water content the product does not ignite.	
<i>Information on: Water</i>		
Vapour pressure:	23.4 hPa ( 20 °C) Literature data.	
-----		
Density:	approx. 0.90 - 0.95 g/cm <sup>3</sup> ( 20 °C)	
Relative density:	No data available.	
Vapour density:	not determined	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	No decomposition if used correctly.	
Viscosity, dynamic:	approx. 250 - 2,000 mPa.s	
Solubility in water:	( 15 °C) partly soluble	
Miscibility with water:	miscible	
Molar mass:	No data available.	
Evaporation rate:	No data available.	
Other Information:	Range of particle size: < 0,1 µm - 10 µm	

### 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

Oxidizing properties:

not fire-propagating

#### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

# Safety Data Sheet

## Butonal® NX 4190

Revision date : 2022/04/07

Version: 5.0

Page: 7/10

(30508809/SDS\_GEN\_MX/EN)

No hazardous reactions when stored and handled according to instructions. After long storage, slight quantities of carbon monoxide may be formed.

The product is chemically stable.

### Conditions to avoid

Avoid extreme heat.

### Incompatible materials

metal salts

### Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon dioxide, carbon monoxide, hydrocarbons

Thermal decomposition:

No decomposition if used correctly.

---

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact. Virtually nontoxic by inhalation. Ingestion may cause gastrointestinal disturbances. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

#### Oral

Type of value: LD50

Species: rat

Value: > 2,000 - 10,000 mg/kg

#### Inhalation

Type of value: ATE

Value: > 5 mg/l

Exposure time: 4 h

Determined for mist

#### Dermal

Type of value: ATE

Value: > 5,000 mg/kg

#### Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

#### Irritation / corrosion

# Safety Data Sheet

## Butonal® NX 4190

Revision date : 2022/04/07  
Version: 5.0

Page: 8/10  
(30508809/SDS\_GEN\_MX/EN)

Assessment of irritating effects: Irritating to eyes. Irritating to skin. If the product adheres to skin, irritation may occur when it dries. The product has not been tested. The statement has been derived from the properties of the individual components.

### Eye

*Information on: Ethanol*  
*Species: rabbit*  
*Result: Irritant.*  
*Method: OECD Guideline 405*  
-----

### Sensitization

Assessment of sensitization: Skin sensitizing effects were not observed in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

### Aspiration Hazard

not applicable

## **Chronic Toxicity/Effects**

### Repeated dose toxicity

Assessment of repeated dose toxicity: No adverse effects were observed after repeated exposure in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

### Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in bacteria. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

### Carcinogenicity

Assessment of carcinogenicity: The whole of the information assessable provides no indication of a carcinogenic effect.

### Reproductive toxicity

Assessment of reproduction toxicity: Not expected to cause reproductive toxicity (based on composition).

### Teratogenicity

Assessment of teratogenicity: The data available for an assessment of the effect of the substance on developmental toxicity are not sufficient for a proper evaluation.

---

## **12. Ecological Information**

### **Toxicity**

#### Aquatic toxicity

Assessment of aquatic toxicity:  
Acutely toxic for aquatic organisms. May cause long-term adverse effects in the aquatic environment. The product has not been tested. The statement has been derived from the properties of the individual components.

#### Toxicity to fish

LC50 (96 h) 1 - 10 mg/l, Fish (OECD Guideline 203, static)



# Safety Data Sheet

## Butonal® NX 4190

Revision date : 2022/04/07  
Version: 5.0

Page: 9/10  
(30508809/SDS\_GEN\_MX/EN)

The product has not been tested. The statement has been derived from the properties of the individual components.

### Persistence and degradability

#### Assessment biodegradation and elimination (H<sub>2</sub>O)

The polymer component of the product is poorly biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

### Bioaccumulative potential

#### Bioaccumulation potential

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

### Mobility in soil

#### Assessment transport between environmental compartments

No data available.

### Additional information

Adsorbable organically-bound halogen (AOX):  
No data available.

Other ecotoxicological advice:  
Do not release untreated into natural waters. At the present state of knowledge, no negative ecological effects are expected.

Ecological data are determined by analogy.

---

## 13. Disposal considerations

### **Waste disposal of substance:**

Must be sent to a suitable incineration plant, observing local regulations.  
Incinerate or dispose of in a licensed facility. Do not discharge into drains/surface waters/groundwater.

### **Container disposal:**

Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

---

## 14. Transport Information

### **Land transport**

TDG

Not classified as a dangerous good under transport regulations

### **Sea transport**

IMDG

Not classified as a dangerous good under transport regulations

# Safety Data Sheet

## Butonal® NX 4190

Revision date : 2022/04/07  
Version: 5.0

Page: 10/10  
(30508809/SDS\_GEN\_MX/EN)

**Air transport**  
IATA/ICAO

Not classified as a dangerous good under transport regulations

---

### 15. Regulatory Information

#### Federal Regulations

Not applicable

#### **NFPA Hazard codes:**

Health: 2      Fire: 1      Reactivity: 0      Special:

---

### 16. Other Information

#### **SDS Prepared by:**

BASF NA Product Regulations  
SDS Prepared on: 2022/04/07

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

Butonal® NX 4190 is a registered trademark of BASF Mexicana or BASF SE

This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET