

# Safety Data Sheet

## Basonat® HI 100 NG

Revision date : 2021/11/18  
Version: 5.0

Page: 1/11  
(30567108/SDS\_GEN\_MX/EN)

### 1. Identification

#### Product identifier used on the label

## Basonat® HI 100 NG

#### Recommended use of the chemical and restriction on use

Recommended use\*: Intermediate (isolated), Hardener for coating materials or adhesives for industrial or professional use, Isocyanate used in the manufacturing of polyurethanes

Recommended use\*: Intermediate (isolated); Hardener for coating materials or adhesives for industrial or professional use

Unsuitable for use: consumer

Suitable for use in industrial sector: chemical industry

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF Mexicana S.A. de C.V.  
Av. Insurgentes Sur 975  
Col. CD. De Los Deportes,  
C.P. 03710 Ciudad de México  
MÉXICO

Telephone: +52 55 5325 2600

#### Emergency telephone number

##### 24 Hour Emergency Response Information

SETIQ: 1800-00-214-(Rep. Mexicana) or 55-59-15-88 (CDMX)  
Telephone: +1-800-849-5204 or +1-833-229-1000

#### Other means of identification

Chemical family: polyfunctional polyisocyanate

---

### 2. Hazards Identification

#### According to Regulation NOM-018-STPS-2015

#### Classification of the product

# Safety Data Sheet

## Basonat® HI 100 NG

Revision date : 2021/11/18  
Version: 5.0

Page: 2/11  
(30567108/SDS\_GEN\_MX/EN)

Acute Tox.	4 (Inhalation - mist)	Acute toxicity
Skin Sens.	1	Skin sensitization
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure

### Label elements

Pictogram:



Signal Word:  
Warning

Hazard Statement:

H332	Harmful if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

Precautionary Statements (Prevention):

P280	Wear protective gloves.
P271	Use only outdoors or in a well-ventilated area.
P260	Do not breathe mist or vapour.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P312	Call a POISON CENTER or physician if you feel unwell.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.
------	---

### Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

---

## 3. Composition / Information on Ingredients

### According to Regulation NOM-018-STPS-2015

(OLIGOMER) Hexamethylene diisocyanate isocyanurate-type oligomers

CAS Number: 28182-81-2

Content (W/W): >= 95.0 - <= 100.0%

Synonym: No data available.

1,6-hexamethylene diisocyanate

CAS Number: 822-06-0

# Safety Data Sheet

## Basonat® HI 100 NG

Revision date : 2021/11/18  
Version: 5.0

Page: 3/11  
(30567108/SDS\_GEN\_MX/EN)

Content (W/W):  $\geq 0.0 - < 0.1\%$   
Synonym: Hexamethylene diisocyanate

---

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

Immediately remove contaminated clothing.

##### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Remove contact lenses, if present. If symptoms persist, seek medical advice.

##### If swallowed:

Immediately rinse mouth and then drink 200 - 300 ml water, do not induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

#### Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

*Information on: (OLIGOMER) Hexamethylene diisocyanate isocyanurate-type oligomers*

*Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps*

*Information on: 1,6-hexamethylene diisocyanate*

*Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps*

#### Indication of any immediate medical attention and special treatment needed

##### Note to physician

Treatment: Inhale corticosteroid dose aerosol. Treat according to symptoms (decontamination, vital functions), no known specific antidote, administer corticosteroid dose aerosol to prevent pulmonary edema.

---

### 5. Fire-Fighting Measures

#### Extinguishing media

Suitable extinguishing media:  
dry powder, foam

Unsuitable extinguishing media for safety reasons:  
No data available.

#### Special hazards arising from the substance or mixture

# Safety Data Sheet

## Basonat® HI 100 NG

Revision date : 2021/11/18  
Version: 5.0

Page: 4/11  
(30567108/SDS\_GEN\_MX/EN)

Hazards during fire-fighting:  
harmful vapours

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Wear a self-contained breathing apparatus.

### Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

### Impact Sensitivity:

Remarks: Based on the chemical structure there is no shock-sensitivity.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

#### Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

#### Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

---

## 7. Handling and Storage

### Precautions for safe handling

Keep away from sources of ignition - No smoking.

### Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

---

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

1,6-hexamethylene diisocyanate      OEL, MX:      TWA value 0.005 ppm ;

### Advice on system design:

Ensure adequate ventilation.

### Personal protective equipment

#### Respiratory protection:

Respiratory protection in case of vapour/aerosol release. Combination filter for gases/vapours of organic compounds and solid and liquid particles (f.e. EN 14387 Type A-P2)

# Safety Data Sheet

## Basonat® HI 100 NG

Revision date : 2021/11/18  
Version: 5.0

Page: 5/11  
(30567108/SDS\_GEN\_MX/EN)

**Hand protection:**

Chemical resistant protective gloves

**Eye protection:**

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

**Body protection:**

Impermeable protective clothing

**General safety and hygiene measures:**

Handle in accordance with good industrial hygiene and safety practice.

### 9. Physical and Chemical Properties

Form:	liquid	
Odour:	almost odourless	
Odour threshold:	Not determined due to potential health hazard by inhalation.	
Colour:	colourless to yellowish	
pH value:	not applicable	
solidification temperature:	-70 °C	(DSC (DIN 51007))
Melting point:	No applicable information available.	
Boiling range:	300 - 355 °C	
Sublimation point:	No applicable information available.	
Flash point:	237.5 °C	(ISO 2719)
Flammability:	not flammable	
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	438 °C	(DIN EN 14522)
Vapour pressure:	3 mbar ( 20 °C)	
Density:	1.168 g/cm <sup>3</sup> ( 20 °C)	(ISO 2811-3)
Relative density:	1.168 ( 20 °C)	
Vapour density:	not determined	
Partitioning coefficient n-octanol/water (log Pow):	9.81	(calculated)
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	140 °C, 10 kJ/kg (DSC (DIN 51007)) The indicated value is for inert gas atmosphere. 290 °C, 280 kJ/kg (DSC (DIN 51007)) The indicated value is for inert gas atmosphere. 425 °C, > 70 kJ/kg (DSC (DIN 51007)) The indicated value is for inert gas atmosphere. 20 - 145 °C, 0 kJ/kg (Warm storage test) No exothermic decomposition within the mentioned temperature range. 125 °C, 550 J/g (DSC (DIN 51007)) Oxidization on contact with air above the mentioned temperature.	

# Safety Data Sheet

## Basonat® HI 100 NG

Revision date : 2021/11/18  
Version: 5.0

Page: 6/11  
(30567108/SDS\_GEN\_MX/EN)

Viscosity, dynamic:	2,500 - 4,000 mPa.s ( 23 °C)	(DIN EN ISO 3219, Annex B)
Viscosity, kinematic:	4,760 mm <sup>2</sup> /s ( 20 °C)	
Particle size:	The substance / product is marketed or used in a non solid or granular form.	
Solubility in water:	Reacts with water. not soluble	
Miscibility with water:	Reacts with water.	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	soluble solvent(s): organic solvents,	
Molar mass:	No applicable information available.	
Evaporation rate:	not determined	

## 10. Stability and Reactivity

### Reactivity

Oxidizing properties:  
not fire-propagating

### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### Possibility of hazardous reactions

Reacts with alcohols. Reacts with amines. Reacts with substances which contain active hydrogen.  
Reacts with water, with formation of carbon dioxide. The formation of gaseous decomposition  
products builds up pressure in tightly closed containers.

### Conditions to avoid

Avoid moisture.

### Incompatible materials

water, alcohols, amines

### Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as  
prescribed/indicated.

Thermal decomposition:

140 °C, 2.5 K/min (DSC (DIN 51007))

The indicated value is for inert gas atmosphere.

290 °C, 2.5 K/min (DSC (DIN 51007))

The indicated value is for inert gas atmosphere.

425 °C, 2.5 K/min (DSC (DIN 51007))

The indicated value is for inert gas atmosphere.

20 - 145 °C (Warm storage test)

No exothermic decomposition within the mentioned temperature range.

125 °C, 2.5 K/min (DSC (DIN 51007))

Oxidization on contact with air above the mentioned temperature.

# Safety Data Sheet

## Basonat® HI 100 NG

Revision date : 2021/11/18  
Version: 5.0

Page: 7/11  
(30567108/SDS\_GEN\_MX/EN)

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Acute Toxicity/Effects

##### Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact. Of moderate toxicity after short-term inhalation.

##### Oral

Type of value: LD50

Species: rat (female)

Value: > 2,500 mg/kg (OECD Guideline 423)

##### Inhalation

Type of value: LC50

Species: rat (male/female)

Value: 0.467 mg/l (OECD Guideline 403)

Exposure time: 4 h

The test result applies only to the substance transferred into respirable aerosol (particles < 20 µm). The substance from the isocyanate substance class has been tested in a form (respirable aerosol) that is different from the forms in which the product is placed on the market and used. Therefore, the test result is not adequate for the purpose of classification and labelling of the product. Based on expert judgement and available data, a modified classification and labeling for acute inhalation toxicity is justified. The generation of a respirable aerosol must be prevented!

##### Dermal

Type of value: LD50

Species: rat (male/female)

Value: > 2,000 mg/kg (OECD Guideline 402)

##### Assessment other acute effects

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

##### Irritation / corrosion

Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.

##### Skin

Species: rabbit

Result: Slightly irritating.

Method: OECD Guideline 404

##### Eye

Species: rabbit

Result: Slightly irritating.

Method: OECD Guideline 405

##### Sensitization

Assessment of sensitization: Caused skin sensitization in animal studies.

# Safety Data Sheet

## Basonat® HI 100 NG

Revision date : 2021/11/18  
Version: 5.0

Page: 8/11  
(30567108/SDS\_GEN\_MX/EN)

Guinea pig maximization test  
Species: guinea pig  
Result: sensitizing  
sensitizing effect in animal tests

### Aspiration Hazard

No aspiration hazard expected.

## Chronic Toxicity/Effects

### Repeated dose toxicity

Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation.

### Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture.

### Carcinogenicity

Assessment of carcinogenicity: Study scientifically not justified.

### Reproductive toxicity

Assessment of reproduction toxicity: Study scientifically not justified.

### Teratogenicity

Assessment of teratogenicity: Study scientifically not justified.

---

## 12. Ecological Information

### Toxicity

#### Aquatic toxicity

Assessment of aquatic toxicity:

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. There is a high probability that the product is not acutely harmful to aquatic organisms.

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. The product may hydrolyse. The test result maybe partially due to degradation products.

#### Toxicity to fish

LC0 (96 h)  $\geq$  100 mg/l, Brachydanio rerio (OECD 203; ISO 7346; 92/69/EEC, C.1, static)

The product may hydrolyse. The test result maybe partially due to degradation products. The product has low solubility in the test medium. An eluate has been tested. Nominal concentration.

#### Aquatic invertebrates

EL50 (48 h) 127 mg/l, Daphnia magna (Directive 92/69/EEC, C.2, static)

Nominal concentration. The product may hydrolyse. The test result maybe partially due to degradation products.

#### Aquatic plants

EC50 (72 h)  $>$  1,000 mg/l (growth rate), Scenedesmus subspicatus (OECD Guideline 201, static)

Nominal concentration. The product may hydrolyse. The test result maybe partially due to degradation products.

#### Chronic toxicity to fish



# Safety Data Sheet

## Basonat® HI 100 NG

Revision date : 2021/11/18  
Version: 5.0

Page: 9/11  
(30567108/SDS\_GEN\_MX/EN)

Study not necessary due to exposure considerations.

### Chronic toxicity to aquatic invertebrates

Study not necessary due to exposure considerations.

### Assessment of terrestrial toxicity

No data available concerning terrestrial toxicity.

Study not necessary due to exposure considerations.

## **Microorganisms/Effect on activated sludge**

### Toxicity to microorganisms

OECD Guideline 209 static

activated sludge of a predominantly domestic sewage/EC20 (3 h): 880 mg/l

Nominal concentration. The product may hydrolyse. The test result maybe partially due to degradation products.

## **Persistence and degradability**

### Assessment biodegradation and elimination (H<sub>2</sub>O)

Poorly biodegradable. The product is unstable in water. The elimination data also refer to products of hydrolysis.

### Elimination information

1 % BOD of the ThOD (28 d) (OECD 301D; EEC 92/69, C.4-E) (aerobic, activated sludge, domestic, non-adapted)

### Assessment of stability in water

In contact with water the substance will hydrolyse rapidly.

### Information on Stability in Water (Hydrolysis)

$t_{1/2} < 1$  h, (OECD Guideline 111, pH 4)

$t_{1/2} < 1$  h, (OECD Guideline 111, pH 7)

$t_{1/2} < 1$  h, (OECD Guideline 111, pH 9)

## **Bioaccumulative potential**

### Assessment bioaccumulation potential

Significant accumulation in organisms is not to be expected.

The product has not been tested. The statement has been derived from the structure of the product.

### Bioaccumulation potential

Bioconcentration factor: 367.7, Fish (calculated)

Analogous: Assessment derived from products with similar chemical character.

## **Mobility in soil**

### Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.

No data available.

## **Additional information**

Other ecotoxicological advice:

# Safety Data Sheet

## Basonat® HI 100 NG

Revision date : 2021/11/18  
Version: 5.0

Page: 10/11  
(30567108/SDS\_GEN\_MX/EN)

Do not release untreated into natural waters. The local regulations on waste-water treatment must be followed.

---

### 13. Disposal considerations

---

### 14. Transport Information

#### Land transport TDG

Not classified as a dangerous good under transport regulations

#### Sea transport IMDG

Not classified as a dangerous good under transport regulations

#### Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

---

### 15. Regulatory Information

#### Federal Regulations

Not applicable

#### **NFPA Hazard codes:**

Health: 2      Fire: 1      Reactivity: -W-      Special:

---

### 16. Other Information

#### **SDS Prepared by:**

BASF NA Product Regulations  
SDS Prepared on: 2021/11/18

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

Basonat® HI 100 NG is a registered trademark of BASF Mexicana or BASF SE

# Safety Data Sheet

## Basonat® HI 100 NG

Revision date : 2021/11/18  
Version: 5.0

Page: 11/11  
(30567108/SDS\_GEN\_MX/EN)

This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET