

Safety Data Sheet

Foamaster® MO NXZ NC

Revision date : 2018/08/22

Version: 4.0

Page: 1/9

(30586009/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Foamaster® MO NXZ NC

Recommended use of the chemical and restriction on use

Recommended use*: Raw material; inks; Varnish; additives; defoamer

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: hydrocarbons, non-ionic surfactants, modified silicones

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Aquatic Acute 3 Hazardous to the aquatic environment - acute

Label elements

Hazard Statement:
H402 Harmful to aquatic life.

Precautionary Statements (Prevention):

Safety Data Sheet

Foamaster® MO NXZ NC

Revision date : 2018/08/22
Version: 4.0

Page: 2/9
(30586009/SDS_GEN_US/EN)

P273 Avoid release to the environment.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
64742-52-5	>= 75.0 - <= 85.0%	Distillates (petroleum), hydrotreated heavy naphthenic
Trade Secret	>= 1.0 - <= 5.0%	Metallic Ester

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

If on skin:

Wash thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open. If irritation develops, seek medical attention.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Seek medical attention if necessary.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Safety Data Sheet

Foamaster® MO NXZ NC

Revision date : 2018/08/22
Version: 4.0

Page: 3/9
(30586009/SDS_GEN_US/EN)

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, foam

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
harmful vapours

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

Keep away from sources of ignition - No smoking.

Protection against fire and explosion:
Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds.

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

Protect from temperatures below: -10 °C

Protect from temperatures above: 50 °C

Safety Data Sheet

Foamaster® MO NXZ NC

Revision date : 2018/08/22
Version: 4.0

Page: 4/9
(30586009/SDS_GEN_US/EN)

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Distillates (petroleum), hydrotreated heavy naphthenic	OSHA PEL ACGIH TLV	PEL 500 ppm 2,000 mg/m ³ ; PEL 5 mg/m ³ Mist ; TWA value 5 mg/m ³ Mist ; TWA value 5 mg/m ³ Inhalable fraction ; ; Exposure by all routes should be carefully controlled to levels as low as possible. ; Included in the regulation, but with no data values - See the regulation for further details
Metallic Ester	ACGIH TLV	TWA value 1 mg/m ³ Respirable fraction ; TWA value 3 mg/m ³ Respirable fraction ; TWA value 10 mg/m ³ Inhalable fraction ;

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Safety glasses with side-shields. Wear face shield if splashing hazard exists.

General safety and hygiene measures:

Wear protective clothing as necessary to minimize contact. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:	liquid
Odour:	of petroleum distillate (e.g. gasoline, kerosene)
Odour threshold:	No applicable information available.
Colour:	amber
pH value:	5.5 - 7.5 (20 °C)
flow point:	-15 °C
boiling temperature:	Information applies to the solvent. > 200 °C
Flash point:	151 °C (ASTM D93)
Flammability:	not flammable
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.
Upper explosion limit:	For liquids not relevant for classification and labelling.
Autoignition:	not determined

Safety Data Sheet

Foamaster® MO NXZ NC

Revision date : 2018/08/22
Version: 4.0

Page: 5/9
(30586009/SDS_GEN_US/EN)

Vapour pressure:	not determined	
Density:	approx. 0.85 - 0.91 g/cm ³ (25 °C)	(ISO 2811-3)
Relative density:	0.85 - 0.91 (25 °C)	
	No data available.	
Vapour density:	not determined	
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	100 - 800 mPa*s (25 °C)	(DIN EN ISO 2555)
Solubility in water:	not determined	
Miscibility with water:	of low solubility	
Evaporation rate:	not determined	

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:
not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Reacts with strong oxidizing agents.

Conditions to avoid

None if used for intended purpose.

Incompatible materials

strong oxidizing agents

Hazardous decomposition products

Decomposition products:
No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Safety Data Sheet

Foamaster® MO NXZ NC

Revision date : 2018/08/22
Version: 4.0

Page: 6/9
(30586009/SDS_GEN_US/EN)

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion.

Oral

Type of value: LD50

Value: > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Inhalation

Type of value: LC50

Species: rat

Exposure time: 4 h
not determined

Dermal

Type of value: LD50

Species: rat

not determined

Assessment other acute effects

No data available.

Irritation / corrosion

Assessment of irritating effects: Not irritating to the eyes. Not irritating to the skin.

Skin

Species: rabbit

Result: non-irritant

The product has not been tested. The statement has been derived from the properties of the individual components.

Eye

Species: rabbit

Result: non-irritant

The product has not been tested. The statement has been derived from the properties of the individual components.

Sensitization

Assessment of sensitization: Not expected to cause skin sensitization. The product has not been tested. The statement has been derived from the properties of the individual components.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: The information available on the product provides no indication of toxicity on target organs after repeated exposure.

Genetic toxicity

Assessment of mutagenicity: Based on the ingredients, there is no suspicion of a mutagenic effect.

Carcinogenicity

Assessment of carcinogenicity: None of the components in this product at concentrations greater than 0.1% are listed by IARC; NTP, OSHA or ACGIH as a carcinogen.

Safety Data Sheet

Foamaster® MO NXZ NC

Revision date : 2018/08/22
Version: 4.0

Page: 7/9
(30586009/SDS_GEN_US/EN)

Reproductive toxicity

Assessment of reproduction toxicity: Based on the ingredients, there is no suspicion of a toxic effect on reproduction.

Teratogenicity

Assessment of teratogenicity: Based on the ingredients, there is no suspicion of a teratogenic effect.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

The product has not been tested. The statement has been derived from the properties of the individual components.

Toxicity to fish

LC50 (96 h) > 100 mg/l, Fish

The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic invertebrates

LC50 (48 h), daphnia
not determined

Aquatic plants

EC50 (72 h), algae
not determined

Chronic toxicity to fish

No data available.

Chronic toxicity to aquatic invertebrates

No data available.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

EC0: > 10 - 100 mg/l

The product has not been tested. The statement has been derived from the properties of the individual components.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Not readily biodegradable (by OECD criteria). The product has not been tested. The statement has been derived from the properties of the individual components.

Bioaccumulative potential

Safety Data Sheet

Foamaster® MO NXZ NC

Revision date : 2018/08/22
Version: 4.0

Page: 8/9
(30586009/SDS_GEN_US/EN)

Assessment bioaccumulation potential

The product has not been tested.

Mobility in soil

Assessment transport between environmental compartments

No data available.

Additional information

Add. remarks environm. fate & pathway:

Treatment in biological waste water treatment plants has to be performed according to local and administrative regulations.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater.

Container disposal:

Recommend crushing, puncturing or other means to prevent unauthorized use of used containers. Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

State regulations

Safety Data Sheet

Foamaster® MO NXZ NC

Revision date : 2018/08/22
Version: 4.0

Page: 9/9
(30586009/SDS_GEN_US/EN)

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
NJ	64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic
PA	64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including ETHYLENE OXIDE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 1 Fire: 1 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2018/08/22

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Foamaster® MO NXZ NC is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET