

# Safety Data Sheet

## Acrodur® POWER 4444 X

Revision date : 2018/11/12

Version: 2.2

Page: 1/9

(30648345/SDS\_GEN\_MX/EN)

### 1. Identification

#### Product identifier used on the label

## Acrodur® POWER 4444 X

#### Recommended use of the chemical and restriction on use

Recommended use\*: Raw material

Suitable for use in industrial sector: chemical industry

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF Mexicana S.A. de C.V.  
Av. Insurgentes Sur 975  
Col. CD. De Los Deportes,  
C.P. 03710 Ciudad de México  
MÉXICO

Telephone: +52 55 5325 2600

#### Emergency telephone number

SETIQ: 1800-00-214-(Rep. Mexicana) or 55-59-15-88 (CDMX)

Telephone: +1-800-849-5204 or +1-833-229-1000

#### Other means of identification

Chemical family: Polymer, dispersion

---

### 2. Hazards Identification

#### According to Regulation NOM-018-STPS-2015

#### Classification of the product

No need for classification according to GHS criteria for this product.

#### Label elements

The product does not require a hazard warning label in accordance with GHS criteria.

# Safety Data Sheet

## Acrodur® POWER 4444 X

Revision date : 2018/11/12  
Version: 2.2

Page: 2/9  
(30648345/SDS\_GEN\_MX/EN)

### Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered. If the product adheres to skin, irritation may occur when it dries.

#### Labeling of special preparations (GHS):

Product contains the following components and may cause an allergic skin reaction: mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

The substance may cause sensitization of the skin in particularly sensitive individuals. Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### 3. Composition / Information on Ingredients

#### According to Regulation NOM-018-STPS-2015

| <u>CAS Number</u> | <u>Weight %</u> | <u>Chemical name</u>   |
|-------------------|-----------------|--|
| 55965-84-9        | 0.0 - < 50.0PPM | mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) |

The product contains:

| <u>CAS Number</u> | <u>Weight %</u> | <u>Chemical name</u> |
|-------------------|-----------------|----------------------|
| Trade Secret      | 40.0 - 60.0%    | Acrylic polymer      |
| 7732-18-5         | 40.0 - 60.0%    | Water                |

### 4. First-Aid Measures

#### Description of first aid measures

##### **General advice:**

Remove contaminated clothing.

##### **If inhaled:**

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

##### **If on skin:**

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

##### **If in eyes:**

Flush with copious amounts of water for at least 15 minutes. If irritation develops, seek medical attention.

##### **If swallowed:**

Immediately rinse mouth and then drink plenty of water, do not induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

#### **Most important symptoms and effects, both acute and delayed**

Symptoms: No significant symptoms are expected due to the non-classification of the product.

# Safety Data Sheet

## Acrodur® POWER 4444 X

Revision date : 2018/11/12  
Version: 2.2

Page: 3/9  
(30648345/SDS\_GEN\_MX/EN)

Hazards: No hazards anticipated.

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Symptomatic treatment (decontamination, vital functions).

---

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
water spray, foam, dry powder

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
No particular hazards known.

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.  
Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered.

---

## 6. Accidental release measures

### Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

### Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Avoid contact with skin and eyes.

### Environmental precautions

Do not release untreated into natural waters.

### Methods and material for containment and cleaning up

For small amounts: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr). Dispose of absorbed material in accordance with regulations.  
For large amounts: Pump off product.

Spills should be contained, solidified, and placed in suitable containers for disposal.

---

## 7. Handling and Storage

### Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. No special measures necessary provided product is used correctly. Ensure adequate ventilation.

### Conditions for safe storage, including any incompatibilities

# Safety Data Sheet

## Acrodur® POWER 4444 X

Revision date : 2018/11/12  
Version: 2.2

Page: 4/9  
(30648345/SDS\_GEN\_MX/EN)

Further information on storage conditions: Store protected against freezing.  
Protect from temperatures below: 5 °C  
The packed product is destroyed at low temperatures or by frost.  
Protect from temperatures above: 60 °C  
The packed product must be protected against exceeding the indicated temperature.

### 8. Exposure Controls/Personal Protection

No occupational exposure limits known.

**Advice on system design:**  
Ensure adequate ventilation.

#### Personal protective equipment

**Respiratory protection:**  
Wear respiratory protection if ventilation is inadequate.

**Hand protection:**  
Chemical resistant protective gloves

**Eye protection:**  
Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

**General safety and hygiene measures:**  
Hands and/or face should be washed before breaks and at the end of the shift. Avoid contact with skin and eyes.

### 9. Physical and Chemical Properties

Form: liquid, dispersion  
Odour: faint odour  
Odour threshold: No data available.  
Colour: white to cream  
pH value: 3 - 5  
( 22 °C)

*Information on: Water*

Melting point: 0 °C

*Information on: Water*

Boiling point: 100 °C

Flash point: > 300 °F (Unspecified)

Flammability: not flammable

Lower explosion limit: not applicable

Upper explosion limit: not applicable

*Information on: Water*

Vapour pressure: 23.4 hPa  
( 20 °C)  
Literature data.

Density: 1.03 g/cm<sup>3</sup>  
( 22 °C)

# Safety Data Sheet

## Acrodur® POWER 4444 X

Revision date : 2018/11/12

Page: 5/9

Version: 2.2

(30648345/SDS\_GEN\_MX/EN)

---

|   |  |
|---|--|
| Relative density:                                   | 1.03<br>( 22 °C)                         |
| Vapour density:                                     | not determined                           |
| Partitioning coefficient n-octanol/water (log Pow): | not applicable                           |
| Self-ignition temperature:                          | not self-igniting                        |
| Viscosity, dynamic:                                 | approx. < 400 mPa.s<br>( 22 °C)          |
| Solubility in water:                                | insoluble                                |
| Miscibility with water:                             | immiscible                               |
| Evaporation rate:                                   | No data available.                       |
| Other Information:                                  | Range of particle size: < 0,1 µm - 10 µm |

---

### 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

Oxidizing properties:

not fire-propagating

#### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions. After long storage, slight quantities of carbon monoxide may be formed.

The product is chemically stable.

#### Conditions to avoid

Avoid extreme heat.

#### Incompatible materials

metal salts

#### Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon dioxide, carbon monoxide, hydrocarbons

---

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Acute Toxicity/Effects

Acute toxicity

# Safety Data Sheet

## Acrodur® POWER 4444 X

Revision date : 2018/11/12  
Version: 2.2

Page: 6/9  
(30648345/SDS\_GEN\_MX/EN)

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact. Virtually nontoxic by inhalation. Ingestion may cause gastrointestinal disturbances. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

### Oral

Type of value: LD50  
Species: rat  
Value: > 2,000 - 10,000 mg/kg

### Inhalation

Type of value: ATE  
Value: > 5 mg/l  
Exposure time: 4 h  
Determined for mist

### Dermal

Type of value: ATE  
Value: > 5,000 mg/kg

### Assessment other acute effects

Assessment of STOT single:  
Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

### Irritation / corrosion

Assessment of irritating effects: Not irritating to eyes and skin. May cause mechanical irritation. If the product adheres to skin, irritation may occur when it dries. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

### Skin

Species: rabbit  
Result: non-irritant  
Method: OECD Guideline 404

### Eye

Species: rabbit  
Result: non-irritant  
Method: OECD Guideline 405

### Sensitization

Assessment of sensitization: The product contains a mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1) (CAS-No.:55965-84-9). The substance may cause sensitization of the skin in particularly sensitive individuals. Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### Aspiration Hazard

not applicable

## **Chronic Toxicity/Effects**

### Repeated dose toxicity

Assessment of repeated dose toxicity: No adverse effects were observed after repeated exposure in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

# Safety Data Sheet

## Acrodur® POWER 4444 X

Revision date : 2018/11/12  
Version: 2.2

Page: 7/9  
(30648345/SDS\_GEN\_MX/EN)

### Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in bacteria. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

### Carcinogenicity

Assessment of carcinogenicity: The whole of the information assessable provides no indication of a carcinogenic effect.

### Reproductive toxicity

Assessment of reproduction toxicity: Not expected to cause reproductive toxicity (based on composition).

### Teratogenicity

Assessment of teratogenicity: The data available for an assessment of the effect of the substance on developmental toxicity are not sufficient for a proper evaluation.

### Experiences in humans

According to experience, the product is considered to be harmless to health if used in the correct manner.

### Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The statement was derived from products of similar composition.

## **Symptoms of Exposure**

No significant symptoms are expected due to the non-classification of the product.

---

## **12. Ecological Information**

### **Toxicity**

#### Toxicity to fish

LC50 (96 h) > 100 mg/l, Brachydanio rerio (OECD Guideline 203, static)

#### Aquatic invertebrates

EC50 (48 h) > 100 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)

#### Aquatic plants

EC50 (72 h) > 100 mg/l, Scenedesmus subspicatus (OECD Guideline 201)  
Nominal concentration.

### **Microorganisms/Effect on activated sludge**

#### Toxicity to microorganisms

DIN EN ISO 8192-OECD 209-88/302/EEC,P. C activated sludge, domestic/EC20 (0.5 h): > 100 mg/l

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

### **Persistence and degradability**

#### Assessment biodegradation and elimination (H2O)

# Safety Data Sheet

## Acrodur® POWER 4444 X

Revision date : 2018/11/12  
Version: 2.2

Page: 8/9  
(30648345/SDS\_GEN\_MX/EN)

The polymer component of the product is poorly biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

### Elimination information

Not readily biodegradable.

### **Bioaccumulative potential**

#### Bioaccumulation potential

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

### **Mobility in soil**

#### Assessment transport between environmental compartments

No data available.

### **Additional information**

Adsorbable organically-bound halogen (AOX):  
No data available.

Other ecotoxicological advice:  
Do not release untreated into natural waters. At the present state of knowledge, no negative ecological effects are expected.

Ecological data are determined by analogy.

---

## 13. Disposal considerations

### **Waste disposal of substance:**

Incinerate or dispose of in a licensed facility. Do not discharge into drains/surface waters/groundwater.

### **Container disposal:**

Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

---

## 14. Transport Information

### **Land transport**

TDG

Not classified as a dangerous good under transport regulations

### **Sea transport**

IMDG

Not classified as a dangerous good under transport regulations

### **Air transport**

IATA/ICAO

Not classified as a dangerous good under transport regulations



# Safety Data Sheet

## Acrodur® POWER 4444 X

Revision date : 2018/11/12  
Version: 2.2

Page: 9/9  
(30648345/SDS\_GEN\_MX/EN)

---

### 15. Regulatory Information

#### Federal Regulations

Not applicable

#### **NFPA Hazard codes:**

Health: 1      Fire: 0      Reactivity: 0      Special:

---

### 16. Other Information

#### **SDS Prepared by:**

BASF NA Product Regulations  
SDS Prepared on: 2018/11/12

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

Acrodur® POWER 4444 X is a registered trademark of BASF Mexicana or BASF SE

This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET