

Safety Data Sheet

Efka® PX 4787

Revision date : 2018/10/08

Version: 1.0

Page: 1/10

(30701302/SDS_GEN_MX/EN)

1. Identification

Product identifier used on the label

Efka® PX 4787

Recommended use of the chemical and restriction on use

Recommended use*: Dispersant in automotive coatings, Dispersant in automotive refinish coatings
Recommended use*: for industrial use only

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF Mexicana S.A. de C.V.
Av. Insurgentes Sur 975
Col. CD. De Los Deportes,
C.P. 03710 Ciudad de México
MÉXICO

Telephone: +52 55 5325 2600

Emergency telephone number

SETIQ: 1800-00-214-(Rep. Mexicana) or 55-59-15-88 (CDMX)
Telephone: +1-800-849-5204 or +1-833-229-1000

Other means of identification

Chemical family: additives, organic solvents

2. Hazards Identification

According to Regulation NOM-018-STPS-2015

Classification of the product

Flam. Liq.	3	Flammable liquids
STOT SE	3 (Vapours may cause drowsiness and dizziness.)	Specific target organ toxicity — single exposure
Aquatic Acute	3	Hazardous to the aquatic environment - acute

Safety Data Sheet

Efka® PX 4787

Revision date : 2018/10/08

Page: 2/10

Version: 1.0

(30701302/SDS_GEN_MX/EN)

Aquatic Chronic

3

Hazardous to the aquatic environment - chronic

Label elements

Pictogram:



Signal Word:

Warning

Hazard Statement:

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P271 Use only outdoors or in a well-ventilated area.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves and eye/face protection.
P273 Avoid release to the environment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P243 Take action to prevent static discharges.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P240 Ground and bond container and receiving equipment.
P242 Use only non-sparking tools.

Precautionary Statements (Response):

P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370 + P378 In case of fire: Use foam or dry powder for extinction.

Precautionary Statements (Storage):

P233 Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition / Information on Ingredients

According to Regulation NOM-018-STPS-2015

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
-------------------	-----------------	----------------------

Safety Data Sheet

Efka® PX 4787

Revision date : 2018/10/08

Page: 3/10

Version: 1.0

(30701302/SDS_GEN_MX/EN)

123-86-4	>= 25.0 - < 50.0%	n-Butyl acetate
542-28-9	>= 0.3 - < 1.0%	delta-valerolactone

4. First-Aid Measures

Description of first aid measures

General advice:

Immediately remove contaminated clothing.

If on skin:

Wash affected areas thoroughly with soap and water. Seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open. If irritation develops, seek medical attention.

If swallowed:

Immediately rinse mouth and then drink plenty of water, do not induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
dry powder, foam

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

harmful vapours

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

Safety Data Sheet

Efka® PX 4787

Revision date : 2018/10/08

Version: 1.0

Page: 4/10

(30701302/SDS_GEN_MX/EN)

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Breathing protection required.

Can release flammable vapours. Wind direction should be noted. Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling

Ensure thorough ventilation of stores and work areas.

Protection against fire and explosion:

Sources of ignition should be kept well clear. Take precautionary measures against static discharges. If delivered in plastic packing, highest permissible emptying temperature is 5 Kelvin below the flash point.

Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Keep container tightly closed and in a cool place.

Protect from temperatures below: -5 °C

Protect from temperatures above: 60 °C

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

n-Butyl acetate	Exposure limits	STEL value 200 ppm ; TWA value 150 ppm ;
-----------------	-----------------	--

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Respiratory protection in case of vapour/aerosol release. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection:

Chemical resistant protective gloves

Safety Data Sheet

Efka® PX 4787

Revision date : 2018/10/08

Version: 1.0

Page: 5/10

(30701302/SDS_GEN_MX/EN)

Eye protection:

Safety glasses with side-shields. Wear face shield if splashing hazard exists.

Body protection:

Impermeable protective clothing

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	ester-like	
Odour threshold:	No applicable information available.	
Colour:	yellow to brownish	
pH value:	not determined	
solidification temperature:	-77 °C (1.013 hPa)	(other)
boiling temperature:	Information applies to the solvent. 124 - 128 °C (1,013 hPa)	(other)
Flash point:	Information applies to the solvent. 25 °C	
Flammability:	Information applies to the solvent. Flammable.	
Lower explosion limit:	1.2 %(V) The lower explosion point of the substance/mixture has been determined. The explosion point describes the temperature of a flammable liquid at which the concentration of the saturated vapour mixed with air equals the lower explosion limit. Information applies to the solvent.	
Upper explosion limit:	7.6 %(V) The upper explosion point of the substance/mixture has been determined. This explosion point describes the temperature of a flammable liquid at which the concentration of the saturated vapour mixed with air equals the upper explosion limit. Information applies to the solvent.	
Autoignition:	370 °C Information applies to the solvent.	
Vapour pressure:	< 20 hPa (20 °C)	
Density:	1.0276 g/cm ³ (20 °C, 1.013 hPa)	(ISO 2811-3)
	0.9995 g/cm ³ (50 °C, 1.013 hPa)	(ISO 2811-3)
Vapour density:	not determined	
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	

Safety Data Sheet

Efka® PX 4787

Revision date : 2018/10/08

Version: 1.0

Page: 6/10

(30701302/SDS_GEN_MX/EN)

Self-ignition temperature:	not self-igniting	
Thermal decomposition:	not determined	
Viscosity, dynamic:	1,684 mPa.s (23 °C)	(DIN 53019)
Solubility in water:	not soluble	
Solubility (quantitative):	insoluble	
Solubility (qualitative):	soluble	
Evaporation rate:	solvent(s): organic solvents, not determined	

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:
not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.
The product is chemically stable.

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

strong acids, strong oxidizing agents

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
not determined

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion.

Oral

Type of value: LD50

Safety Data Sheet

Efka® PX 4787

Revision date : 2018/10/08

Page: 7/10

Version: 1.0

(30701302/SDS_GEN_MX/EN)

Species: rat

Value: > 5,000 mg/kg (other)

The product has not been tested. The statement has been derived from the properties of the individual components.

Inhalation

Type of value: LC50

Species: rat

Exposure time: 4 h

not determined

Dermal

Type of value: LD50

Species: rat

not determined

Assessment other acute effects

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion

Assessment of irritating effects: Not irritating to eyes and skin.

Skin

Species: rabbit

Result: non-irritant

Method: other

The product has not been tested. The statement has been derived from the properties of the individual components.

Eye

Species: rabbit

Result: non-irritant

Method: other

The product has not been tested. The statement has been derived from the properties of the individual components.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: The information available on the product provides no indication of toxicity on target organs after repeated exposure.

Genetic toxicity

Assessment of mutagenicity: Based on the ingredients, there is no suspicion of a mutagenic effect.

Carcinogenicity

Assessment of carcinogenicity: The whole of the information assessable provides no indication of a carcinogenic effect.

Reproductive toxicity

Assessment of reproduction toxicity: Based on the ingredients, there is no suspicion of a toxic effect on reproduction.

Safety Data Sheet

Efka® PX 4787

Revision date : 2018/10/08

Version: 1.0

Page: 8/10

(30701302/SDS_GEN_MX/EN)

Teratogenicity

Assessment of teratogenicity: Based on the ingredients, there is no suspicion of a teratogenic effect.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Toxicity

Toxicity to fish

LC50 (96 h) 10 - 100 mg/l, Fish (other, other)

The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic invertebrates

LC50 (48 h), daphnia

not determined

Aquatic plants

EC50 (72 h), algae

not determined

Chronic toxicity to fish

No data available.

Chronic toxicity to aquatic invertebrates

No data available.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

bacteria/EC50 (0.5 h):

not determined

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Product is not expected to be readily biodegradable. The product has not been tested.

Bioaccumulative potential

Assessment bioaccumulation potential

The product has not been tested.

Mobility in soil

Assessment transport between environmental compartments

No data available.

Additional information

Add. remarks environm. fate & pathway:

Safety Data Sheet

Efka® PX 4787

Revision date : 2018/10/08

Page: 9/10

Version: 1.0

(30701302/SDS_GEN_MX/EN)

Treatment in biological waste water treatment plants has to be performed according to local and administrative regulations.

Other ecotoxicological advice:

Do not discharge product into the environment without control.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations.

Container disposal:

Uncontaminated packaging can be re-used. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

WARNING: Empty containers may still contain hazardous residue.

14. Transport Information

Land transport

TDG

Hazard class: 3
Packing group: III
ID number: UN 1123
Hazard label: 3
Proper shipping name: BUTYL ACETATES

Sea transport

IMDG

Hazard class: 3
Packing group: III
ID number: UN 1123
Hazard label: 3
Marine pollutant: NO
Proper shipping name: BUTYL ACETATES

Air transport

IATA/ICAO

Hazard class: 3
Packing group: III
ID number: UN 1123
Hazard label: 3
Proper shipping name: BUTYL ACETATES

15. Regulatory Information

Federal Regulations

Not applicable

Safety Data Sheet

Efka® PX 4787

Revision date : 2018/10/08

Version: 1.0

Page: 10/10

(30701302/SDS_GEN_MX/EN)

NFPA Hazard codes:

Health: 2

Fire: 3

Reactivity: 0

Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2018/10/08

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Efka® PX 4787 is a registered trademark of BASF Mexicana or BASF SE

This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET