


Efka® PU 4061



Polyurethane-based high-molecular weight dispersing agent with excellent low mill base viscosity for solvent-based systems

Efka® PU 4061 is a polymeric dispersing agent for stabilizing inorganic and organic pigments. It is used in all types of solvent-based coatings, particularly high-quality industrial coatings such as automotive topcoats (OEM and refinish), coil coatings and 2-pack polyurethane coating systems. Efka® PU 4061 is designed to be used in combination with high performance organic pigments.


Efka® PU 4061 shows excellent low mill base viscosity RMPC – Chromophtal Red A2B



Performance Highlights

- Excellent low mill-base viscosity
- Reduced grinding time and optimized processing efficiency
- Improved gloss and DOI (distinct of image)
- Excellent shelf stability, also at low temperature conditions
- Reduced flooding problems
- Higher color strength

Efka® PU 4061: Elongated side chains for improved steric hindrance




Efka® PU 4061 demonstrates excellent shelf stability, also at low temperature conditions



Efka® PU 4061: Characteristic Values

Property	Value
Appearance	clear to slightly hazy yellowish liquid
Color Gardner	<= 6
Density	~ 0.95 g/cm ³
Solids	~ 30.0%



Contacts worldwide

Asia

BASF East Asia Regional Headquarters Ltd.
45/F., Jardine House
No. 1 Connaught Place
Central
Hong Kong
formulation-additives-asia@basf.com

Europe

BASF SE
Formulation Additives
67056 Ludwigshafen
Germany
formulation-additives-europe@basf.com

North America

BASF Corporation
11501 Steele Creek Road
Charlotte, NC 28273
USA
formulation-additives-nafta@basf.com

South America

BASF S.A.
Rochaverá - Crystal Tower
Av. das Nações Unidas, 14.171
Morumbi - São Paulo-SP
Brazil
formulation-additives-south-america@basf.com

www.basf.com/formulation-additives

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed. When handling these products, advice and information given in the safety data sheet must be complied with. Further, protective and workplace hygiene measures adequate for handling chemicals must be observed.

® = registered trademark of the BASF Group