

# Acronal<sup>®</sup> 3626

## Adhesive Raw Material

**Chemical nature**            Aqueous dispersion of an acrylic ester copolymer

### Properties

**Physical form**            liquid

**Technical data**

(not supply specification)

Solid content	DIN EN ISO 3251	~ 55%
pH value	DIN ISO 976	6.0 – 9.0
Viscosity, dynamic	DIN EN ISO 3219 (23 °C, 250 1/s)	20 – 130 mPa.s
Glass transition temperature		~ 47°C

---

## Application

Acronal® 3626 can be used as a binder for vibration dampening compounds. Such compounds can be formulated with inorganic fillers and various additives such as dispersing agents or thickeners to be applied in liquid form and dried at elevated temperatures. Acoustic compounds formulated with Acronal® 3902 X show maximum vibration dampening in the range of 55 – 65 °C.

## Advantages

Due to its outstanding ability to dampen vibrations Acronal® 3626 can be employed in acoustic compounds. It is especially suited in a mixture with other binders to extend damping performance at temperatures above room temperature.

## Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

## Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = Registered trademark

™ = Trademark of the BASF Group, unless otherwise noted

BASF SE

Dispersions Europe

67056 Ludwigshafen, Germany

[www.basf.com/dispersions](http://www.basf.com/dispersions)