

Acronal[®] 4053 X

Chemical nature

Acronal 4053 X is a water-based dispersion polymer for liquid applied sound damping (LASD) application. It is a medium T_g acrylic dispersion polymer. It has a lower viscosity than Acronal DS 3502 for easier handling and blending.

Properties

Typical Properties

Solids content	%	54 – 58
pH value		5 – 8
Viscosity at 23 °C (Brookfield RV, Spindle #3, at 20 rpm)	cps	200 – 4000
Viscosity at 23 °C (23°C, 250 1/s, DIN EN ISO 3219)	mPa*s	50 – 800

Further properties of the dispersion

Density	g/cm ³	approx. 1.04
Freeze/thaw resistance		not resistant to freezing
Dispersion type		anionic
Glass transition temperature T _g (DSC)	°C	ca. 4

* These typical values should not be interpreted as specifications.

Application

Features

Acronal 4053 X can also be employed in acoustic compounds, which are used in machinery and automotive damping treatments. It is used as a binder for aqueous compounds that are capable of being sprayed. Acoustic compounds formulated with Acronal 4053 X display maximum noise suppression in the 10 – 20 °C range.

Processing

When Acronal 4053 X is mixed with other materials, the final mixture should be adjusted to pH > 6, which increases the mechanical stability.

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care and wearing of protective goggles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Acronal 4053 X.

Storage

Please refer to the "Handling and Storage of polymer dispersions" brochure.

Important

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE.** Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Acronal is a registered trademark of BASF Group.

© BASF Corporation, 2022



BASF Corporation is fully committed to the Responsible Care® Initiative in the USA, Canada, and Mexico.
For more information on Responsible Care® go to:
U.S.: www.basf.us/responsiblecare_usa
Canada: www.basf.us/responsiblecare_canada
México: www.basf.us/responsiblecare_mexico

BASF Corporation
Dispersions and Resins
11501 Steele Creek Road
Charlotte, North Carolina 28273
Phone: (800) 251 – 0612
CustCare-Charlotte@basf.com
Email: edtech_info@basf.com
www.basf.us/dpsolutions