

Acronal[®] EDGE 4750

Chemical Nature

All acrylic latex dispersion intended for interior or exterior premium grade flat through semi-gloss paints

Properties

Typical Properties

Solids content	%	49.0 – 51.0
Solids content, Volume	%	46.0 – 48.0
VOC content, weight	%	< 0.2
VOC content, volume	%	< 0.2
Brookfield Viscosity	cps	< 500cps
pH		7.5 – 8.5

Other properties of the dispersion

Specific gravity	g/cm ³	ca. 1.06
Density	lbs/gal	ca. 8.8
MFFT		ca. 15
Particle size	nm	ca. 120

*These figures should be taken for comparison purposes only. They furnish only a rough comparison of film strengths.

Application

Applications

Acronal EDGE 4750 is engineered specifically to meet all the performance requirements in the market segment "Paint and Primer in One".

Features

Paints formulated with Acronal EDGE 4750 demonstrate the following features:

- Zero VOC Capable
- Wet Adhesion
- Stain Blocking
- Easy Cleaning
- Scrub Resistance
- Block Resistance
- Tannin Blocking
- Dirt Pick Up Resistance.

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care and wearing of protective goggles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Acronal EDGE 4750.

Storage

Storage should be in accordance with the "Handling and Storage of polymer dispersions" brochure. Technical information regarding the storage of BASF polymer dispersion products is available upon request.

Important

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE.** Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Acronal is a registered trademark of BASF Group.

© BASF Corporation, 2018



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico.

For more information on Responsible Care® go to:

U.S.: www.basf.us/responsiblecare_usa

Canada: www.basf.us/responsiblecare_canada

México: www.basf.us/responsiblecare_mexico

BASF Corporation
Dispersions and Resins
11501 Steele Creek Road
Charlotte, North Carolina 28273
Phone: (800) 251 – 0612
Email: DispersionsPigmentsCC@basf.com
Email: edtech-info@basf.com
www.basf.us/formulation-additives