

Acronal[®] MB EDGE 4247

Chai	mical	1 11-4.	
Che	IIICal	Nall	<i>ire</i>

Acrylic latex resin used in architectural coatings.

Acronal® MB(*) EDGE 4247 is identical to Acronal® EDGE 4247, but achieves a significantly lower Product Carbon Footprint, because it uses renewable raw materials instead of fossil raw materials via a mass balance approach.

* MB = Mass Balance

	Properties				
Typical Properties	Solids content, weight	%	52.0 - 54.0		
	Solids content, Volume	%	49.0 - 51.0		
	Brookfield Viscosity	cps	< 1100 cps		
	рН		7.8 – 9.0		
Other properties of	Specific gravity	lbs/gal	ca. 8.9		
the dispersion	MFFT		ca. 7		
	Particle size	nm	ca. 130		
	*These figures should be take comparison of film strengths		purposes only. They furnish only a rough		
	Application				
Applications	Exterior (primary) and Interior Architectural Coatings				
Features	Low VOC capable binder that combines excellent priming capabilities, specifically tannin block and efflorescence resistance with outstanding topcoat properties that include dirt pickup resistance and surfactant leaching resistance.				
	A biomass balance product certified by TÜV Nord according to REDcert2 certification scheme fo the chemical industry. This product entails a 100% substitution of fossil with renewable raw materials in the value chain.				
	Safety				
General	The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care and wearing of protective goggles.				
Safety Data Sheet	All safety information is provided in the Safety Data Sheet for Acronal MB EDGE 4247.				

Storage

Storage should be in accordance with the "Handling and Storage of polymer dispersions" brochure. Technical information regarding the storage of BASF polymer dispersion products is available upon request.

Important

WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, BASF RECOMMENDS THAT THE READER MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR A PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESCRIPTIONS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF BASF'S TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTIONS, DESIGNS, DATA OR INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT THE READER'S RISK.

Acronal is a registered trademark of BASF Group.

© BASF Corporation, 2023



BASF Corporation is fully committed to the Responsible Care[®] initiative in the USA, Canada, and Mexico. For more information on Responsible Care[®] go to: U.S.: www.basf.us/responsiblecare_usa Canada: www.basf.us/responsiblecare_canada México: www.basf.us/responsiblecare_mexico

BASF Corporation

Dispersions and Resins 11501 Steele Creek Road Charlotte, North Carolina 28273 Phone: (800) 251 – 0612 Email: CustCare-Charlotte@basf.com www.basf.us/dpsolutions