

## Dispex® CX 4230

### general

Dispex® CX 4230 is a hydrophobic dispersant for architectural paints and coatings. It offers the following advantages:

- early blister resistance even at high humidity
- excellent gloss development
- excellent color acceptance
- good dispersant efficiency
- very competitive cost performance versus other hydrophobic dispersants

### chemical nature

aqueous solution of polymer

---

## Properties

### physical form

clear, light yellow to amber liquid

### storage

although Dispex® CX 4230 is freeze-thaw stable it should be stored at temperatures above 5°C (41°F) to allow easy handling.

### typical properties (no supply specification)

solids	~ 28 %
pH	~ 8
density at 20°C (68°F)	~ 1.1 g/cm <sup>3</sup>
Brookfield viscosity at 23 °C (73°F)	~ 150 mPa . s

---

## Application

Dispex® CX 4230 is used to disperse titanium dioxide and extender pigments in architectural paints and coatings.

### recommended concentrations

1.0 to 3.0% based on pigment solids

## Contacts worldwide

## Asia

BASF East Asia Regional Headquarters Ltd  
45/F, Jardine House  
No. 1 Connaught Place  
Central Hong Kong  
China  
[formulation-additives-asia@basf.com](mailto:formulation-additives-asia@basf.com)

## Europe

BASF SE  
Formulation Additives  
67056 Ludwigshafen  
Germany  
[formulation-additives-europe@basf.com](mailto:formulation-additives-europe@basf.com)

## North America

BASF Corporation  
11501 Steele Creek Road  
Charlotte, NC 28273  
USA  
[formulation-additives-nafta@basf.com](mailto:formulation-additives-nafta@basf.com)

## South America

BASF S.A  
Rochaverá - Crystal Tower  
Av. das Nações Unidas, 14.171  
Morumbi - São Paulo-SP  
Brazil  
[formulation-additives-south-america@basf.com](mailto:formulation-additives-south-america@basf.com)

**Validity**

This Technical Data Sheet is valid for all versions of the Dispex CX 4230.

**Safety**

When handling these products, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

**Note**

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of BASF Group, unless otherwise noted

[www.basf.com/formulation-additives](http://www.basf.com/formulation-additives)