

Efka® FA 4608

general

low-molecular-weight dispersing agent

Efka® FA 4608 is a wetting and dispersing additive for inorganic pigments (especially TiO₂) and extenders. Product benefits are:

- reduced dispersing time
- increased gloss
- reduced flooding of pigments

In white bases, Efka® FA 4608 improves the color acceptance of tinting pastes, resulting in higher pigment efficiency. In addition it will reduce flooding and floating in those bases.

chemical nature

hydroxy-functional unsaturated modified carboxylic acid with pigment-affine groups

Properties

physical form

clear to slightly hazy brownish liquid

storage

Efka® FA 4608 should be stored in a cool dry place. Storage at temperatures below 10 °C (50 °F) may lead to partial solidification. Reliquefy by heating contents to 35 – 40 C (95 –102 °F).

typical properties (no supply specification)

density at 20 °C (68 °F)	~ 0.95 g/cm ³
active ingredients	~ 100 %
amine value	~ 85 mg KOH/g
color (Gardner)	≤ 13

Application

Efka® FA 4608 is suitable for use in solvent-based architectural and decorative paints.

recommended concentrations

Calculation method for the required amount of active ingredient:

- 0.5 – 1.5 % by weight on TiO₂ or extenders
- 3.0 – 5.0 % by weight on other inorganic pigments

Efka® FA 4608 should be added prior to the dispersing process.

Contacts worldwide

Asia

BASF East Asia Regional Headquarters Ltd
45/F, Jardine House
No. 1 Connaught Place
Central Hong Kong
China
formulation-additives-asia@basf.com

Europe

BASF SE
Formulation Additives
67056 Ludwigshafen
Germany
formulation-additives-europe@basf.com

North America

BASF Corporation
11501 Steele Creek Road
Charlotte, NC 28273
USA
formulation-additives-nafta@basf.com

South America

BASF S.A
Rochaverá - Crystal Tower
Av. das Nações Unidas, 14.171
Morumbi - São Paulo-SP
Brazil
formulation-additives-south-america@basf.com

Validity

This Technical Data Sheet is valid for all versions of the Efka® FA 4608.

Safety

When handling these products, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of BASF Group, unless otherwise noted

www.basf.com/formulation-additives