Technical Information

Efka® PB 2720



defoamer general

supports quick de-aeration of thermosetting resin systems

allows easy processing of foam and blister-free self leveling

compounds and laminates

chemical nature solution of defoaming substances, silicone free

Properties

physical form colorless, clear to slightly hazy liquid

Efka® PB 2720 should be stored in a cool dry place. storage

typical properties (no supply specification)

| solvent | alkyl benzene/ industrial spirit (boiling range 140–165°C) |
|------------------|--|
| density at 20°C | ~ 0.84 g/cm ³ |
| refractive index | 1.474 |
| flash point | 26 °C (79°F) |

Application

Efka® PB 2720 can be used in pigmented or non-pigmented resin systems such as:

- unsaturated polyesters (SMC/BMC gelcoats and synthetic mortars)
- two-pack epoxies
- **PVC-compounds**

If used in combination with Efka® FA 4644 in pigmented compounds, a lower viscosity results thereby aiding the air release properties.

recommended concentrations

0.1-1.0% on total formulation

Efka® PB 2720 should be incorporated by simple mixing. A homogeneous mix will increase the efficiency.

Efka® PB 2720 page 2 of 2 December 2016

Contacts worldwide

Asia

BASF East Asia Regional Headquarters Ltd

45/F, Jardine House No. 1 Connaught Place Central Hong Kong

China

formulation-additives-asia@basf.com

Europe BASF SE

Formulation Additives 67056 Ludwigshafen

Germany

formulation-additives-europe@basf.com

North America **BASF** Corporation 11501 Steele Creek Road Charlotte, NC 28273

USA

formulation-additives-nafta@basf.com

South America BASF S.A

Rochaverá - Crystal Tower Av. das Naçoes Unidas, 14.171 Morumbi - São Paulo-SP

Brazil

formulation-additives-south-america@basf.com

Validity

This Technical Data Sheet is valid for all versions of the Efka® PB 2720.

When handling these products, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and

 $^{^{\}circledR}$ = registered trademark, $^{\intercal M}$ = trademark of BASF Group, unless otherwise noted