

FoamStar® ST 2434

Product description

FoamStar ST 2434 represents a novel series of defoamers based on new defoamer chemistry. It is the first new defoamer chemistry in over 30 years. FoamStar ST 2434 defoamer is effective in high gloss paints and coatings based on acrylic, styrene acrylic and vinyl acrylic latex.

FoamStar is a defoaming molecule that defoams by a different mechanism. Unlike conventional defoamers (mineral oil or silicone), FoamStar defoams on a molecular level. It also has wetting properties not found in other conventional defoamers. FoamStar ST 2434 utilizes the FoamStar Molecule compounded with polysiloxanes in a mineral oil-free system.

Chemical nature

Hyper-branched polymer with organic modified silicones

Properties

Physical form

Opaque, off-white liquid

Technical data (not supply specification)

Active substance	%	100
Density (at 25°C)	lbs/gal	~ 8.1
Viscosity (Brookfield LV)	cps	~ 75 - 105
Dispersibility		non- dispersible

Applications

FoamStar ST 2434 has the following advantages:

- Does not reduce the gloss of high gloss paints and coatings
- Effective in difficult to defoam high gloss formulations.
- Very fast bubble-break versus conventional defoamers
- Effective against Microfoam
- Does not separate or settle
- · Easy to incorporate
- Good persistence
- Effective in white bases and pastes

Formulation guideline

FoamStar ST 2434 can be used at levels of 0.25 % to 0.50 % based on total weight of paint depending on the individual paint formulation. FoamStar ST 2434 addition may be equally divided between the grind and let-down stages. Its effectiveness is the same in the grind and the let-down.

Storage

FoamStar ST 2434 is subject to appropriate storage under the usual storage and temperature conditions, our products are durable for at least 1 year. FoamStar ST 2434 is shipped in 55 gallon (200 liter) steel drums (400 lbs.) and plastic totes (1900 lbs.) and 5-gal pails (40 lbs.). If subjected to below freezing temperatures, product may congeal or stratify. Warm to room temperature and mix well before using.

August 2018 rev 3 page 2 of 2

Contacts worldwide

Asia
BASF East Asia Regional Headquarters Ltd
45/F, Jardine House
No. 1 Connaught Place
Central Hong Kong
China
formulation-additives-asia@basf.com

Europe
BASF SE
Formulation Additives
67056 Ludwigshafen
Germany
formulation-additives-europe@basf.com

North America BASF Corporation 11501 Steele Creek Road Charlotte, NC 28273

 $\underline{formulation\text{-}additives\text{-}nafta@basf.com}$

South America BASF S.A Rochaverá - Crystal Tower Av. das Naçoes Unidas, 14.171 Morumbi - São Paulo-SP Brazil

formulation-additives-south-america@basf.com

Validity

This Technical Data Sheet is valid for all versions of the 0BFoamStar ST 2434.

Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = Registered trademark