

# Foamaster<sup>®</sup> WO 2323

<b>general</b>	defoamer for low-odor emulsion paints
<b>chemical nature</b>	formulation based on white oil and non-ionic surfactants

---

## Properties

<b>physical form</b>	opaque whitish liquid								
<b>storage</b>	Foamaster <sup>®</sup> WO 2323 should be stored in a cool dry place.  During storage of Foamaster <sup>®</sup> WO 2323 a slight sedimentation or phase separation might occur. The defoaming properties of Foamaster <sup>®</sup> WO 2323 are not affected, if the product is mixed thoroughly prior to use.								
<b>typical properties (no supply specification)</b>	<table><tr><td>density at 20 °C (68 °F)</td><td>~ 0.88 g/cm<sup>3</sup></td></tr><tr><td>water content</td><td>~ 0.025%</td></tr><tr><td>dilution appearance at 25°C (77 °F)</td><td>~ 2.5%</td></tr><tr><td>Brookfield viscosity at 23°C (73 °F)</td><td>~ 1,250 mPa · s</td></tr></table>	density at 20 °C (68 °F)	~ 0.88 g/cm <sup>3</sup>	water content	~ 0.025%	dilution appearance at 25°C (77 °F)	~ 2.5%	Brookfield viscosity at 23°C (73 °F)	~ 1,250 mPa · s
density at 20 °C (68 °F)	~ 0.88 g/cm <sup>3</sup>								
water content	~ 0.025%								
dilution appearance at 25°C (77 °F)	~ 2.5%								
Brookfield viscosity at 23°C (73 °F)	~ 1,250 mPa · s								

---

## Application

	Foamaster <sup>®</sup> WO 2323 is a defoamer for manufacturing and application of emulsion paints.
<b>recommended concentrations</b>	0.1 – 0.3% on total formulation

## Contacts worldwide

## Asia

BASF East Asia Regional Headquarters Ltd  
45/F, Jardine House  
No. 1 Connaught Place  
Central Hong Kong  
China  
[formulation-additives-asia@basf.com](mailto:formulation-additives-asia@basf.com)

## Europe

BASF SE  
Formulation Additives  
67056 Ludwigshafen  
Germany  
[formulation-additives-europe@basf.com](mailto:formulation-additives-europe@basf.com)

## North America

BASF Corporation  
11501 Steele Creek Road  
Charlotte, NC 28273  
USA  
[formulation-additives-nafta@basf.com](mailto:formulation-additives-nafta@basf.com)

## South America

BASF S.A  
Rochaverá - Crystal Tower  
Av. das Nações Unidas, 14.171  
Morumbi - São Paulo-SP  
Brazil  
[formulation-additives-south-america@basf.com](mailto:formulation-additives-south-america@basf.com)

**Validity**

This Technical Data Sheet is valid for all versions of the Foamaster® MO 2323.

**Safety**

When handling these products, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

**Note**

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of BASF Group, unless otherwise noted

[www.basf.com/formulation-additives](http://www.basf.com/formulation-additives)