

# Hydropalat<sup>®</sup> WE 3910

<b>Product description</b>	Hydropalat <sup>®</sup> WE 3910 is a nonionic surfactant in powder form used to improve the storage stability of emulsion paints and their compatibility with cement and lime.
<b>Chemical nature</b>	Fatty alcohol ethoxylate

---

## Properties

**Physical form** Powder

<b>Technical data</b>	Bulk density		~ 600 g/l
<b>(not supply specification)</b>	Cloud point	EN 1890 (method B)	90.0 – 94.0 °C
	pH value	EN 1262	5.0 – 8.0

---

## Application

Hydropalat® WE 3910 is a nonionic surfactant in powder form used to improve the storage stability of emulsion paints and their compatibility with cement and lime.

It can be used in interior paints, exterior paints and textured finishes.

Hydropalat® WE 3910 offers performance highlights such as:

- Excellent improvement of compatibility with cement and lime
- Improvement of storage stability
- Easier cleaning of equipment

## Recommended concentrations

An addition level of about 0.3 % – 1.0 % in relation to the final formulation is recommended.

---

## Storage

Subject to appropriate storage under the usual storage and temperature conditions, our product is durable for at least 24 months.

The storage temperature should be kept below 30 °C.

Keep containers tightly closed.

Keep storage temperature below 30 °C.

### Contacts worldwide

Asia  
BASF East Asia Regional Headquarters Limited  
36/F, Two Taikoo Place,  
Taikoo Place,  
979 King's Road,  
Quarry Bay, Hong Kong  
[formulation-additives-asia@basf.com](mailto:formulation-additives-asia@basf.com)

North America  
BASF Corporation  
11501 Steele Creek Road  
Charlotte, NC 28273  
USA  
[formulation-additives-nafta@basf.com](mailto:formulation-additives-nafta@basf.com)

Europe  
BASF SE  
Formulation Additives  
67056 Ludwigshafen  
Germany  
[formulation-additives-europe@basf.com](mailto:formulation-additives-europe@basf.com)

South America  
BASF S.A.  
Rochaverá - Crystal Tower  
Av. das Nações Unidas, 14.171  
Morumbi - São Paulo-SP  
Brazil  
[formulation-additives-south-america@basf.com](mailto:formulation-additives-south-america@basf.com)

### Validity

This Technical Data Sheet is valid for all versions of the Hydropalat® WE 3910.

### Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

### Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = Registered trademark

™ = Trademark of the BASF Group, unless otherwise noted

[www.basf.com/formulation-additives](http://www.basf.com/formulation-additives)