

# Hydropalat® WE 3120

<b>general</b>	low-foaming wetting agent for the printing inks and adhesives industry
	<ul style="list-style-type: none"><li>• low-foaming wetting agent for emulsion paints and fountain solutions</li><li>• very good alkali and acid stability</li><li>• good water solubility</li></ul>
<b>chemical nature</b>	fatty alcohol alkoxyate

---

## Properties

<b>physical form</b>	colorless liquid						
<b>storage</b>	It is recommended to store Hydropalat® WE 3120 at room temperature and to protect the product against heat and frost.						
<b>typical properties (no supply specification)</b>	<table><tr><td>density at 20 °C (68 °F)</td><td>~ 0.956 g/cm<sup>3</sup></td></tr><tr><td>pH value (1%)</td><td>~ 7</td></tr><tr><td>cloud point</td><td>~ 29.5 °C</td></tr></table>	density at 20 °C (68 °F)	~ 0.956 g/cm <sup>3</sup>	pH value (1%)	~ 7	cloud point	~ 29.5 °C
density at 20 °C (68 °F)	~ 0.956 g/cm <sup>3</sup>						
pH value (1%)	~ 7						
cloud point	~ 29.5 °C						

---

## Application

	<p>Hydropalat® WE 3120 is a low-foaming wetting agent and is recommended to be used in the formulation of aqueous paints and printing inks.</p> <p>Hydropalat® WE 3120 can also act as a good antifoam agent in numerous applications.</p>
<b>recommended concentrations</b>	0.5 - 5% on total formulation
	<p>Due to the numerous fields of applications, the optimal dosage of Hydropalat® WE 3120 can vary. Exact levels should be determined by the appropriate testing.</p>

## Contacts worldwide

## Asia

BASF East Asia Regional Headquarters Ltd  
45/F, Jardine House  
No. 1 Connaught Place  
Central Hong Kong  
China  
[formulation-additives-asia@basf.com](mailto:formulation-additives-asia@basf.com)

## North America

BASF Corporation  
11501 Steele Creek Road  
Charlotte, NC 28273  
USA  
[formulation-additives-nafta@basf.com](mailto:formulation-additives-nafta@basf.com)

## Europe

BASF SE  
Formulation Additives  
67056 Ludwigshafen  
Germany  
[formulation-additives-europe@basf.com](mailto:formulation-additives-europe@basf.com)

## South America

BASF S.A  
Rochaverá - Crystal Tower  
Av. das Nações Unidas, 14.171  
Morumbi - São Paulo-SP  
Brazil  
[formulation-additives-south-america@basf.com](mailto:formulation-additives-south-america@basf.com)

**Validity**

This Technical Data Sheet is valid for all versions of the Hydropalat WE 3120.

**Safety**

When handling these products, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

**Note**

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of BASF Group, unless otherwise noted

[www.basf.com/formulation-additives](http://www.basf.com/formulation-additives)