

Joncryl[®] 538-A

Product Description	Joncryl 538-A is an alcohol-resistant, Rheology Controlled (RC) acrylic emulsion for printing ink, overprint varnish applications, and functional packaging coatings.
Key Features & Benefits	<ul style="list-style-type: none">- Good balance of alcohol resistance and resolubility- Resistance to plasticizer migration
Chemical Composition	RC acrylic emulsion

Properties

Typical Properties	Appearance		translucent emulsion
	Non-volatile	%	45.0
	pH at 25°C		9.3
	Viscosity at 25°C	cps	200
	Molecular weight (Mw)		> 200,000
	Acid number (NV)		53
	Density at 25°C	g/cm ³	1.04
	MFFT	°C	65
	Tg	°C	64
	Freeze-thaw stable		Yes
	Total VOC	% wt	1.0

These typical values should not be interpreted as specifications.

Application

Joncryl 538-A is a non-film forming, RC acrylic polymer that can be coalesced to form an alcohol- and chemical-resistant film for inks and coatings. In addition, the unique properties of this polymer include outstanding gloss and adhesion to flexible substrates such as vinyl and polystyrene when formulated with the proper coalescing solvents. The hardness of this polymer allows it to resist plasticizer migration on printed vinyl.

Joncryl 538-A is recommended for applications such as:

- Printing inks
- Overprint varnishes for commercial, publication, or packaging applications
- Functional packaging coatings for heat seal applications

Processing

In addition to surfactant-based pigment dispersions, resinated pigment dispersions (conventional dispersions utilizing acrylic resins) may also be used in inks that are letdown with Joncryl 538-A. However, the alkali resistance will be affected.

The addition of a small amount of amine such as monoethanolamine (MEA) or dimethylethanolamine (DMEA) will increase resolubility on the press and promote release from the anilox cells, but will also have an impact on the final alcohol and water resistance.

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care and wearing of protective goggles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Joncryl 538-A.

Storage

Please refer to the "Handling and Storage of Polymer Dispersions" brochure.

Important

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE.** Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Joncryn is a registered trademark of BASF Group.

© BASF Corporation, 2019



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico.

For more information on Responsible Care® go to:

U.S.: www.basf.us/responsiblecare_usa

Canada: www.basf.us/responsiblecare_canada

México: www.basf.us/responsiblecare_mexico

BASF Corporation

Dispersions and Resins

11501 Steele Creek Road

Charlotte, North Carolina 28273

Phone: (800) 251 – 0612

Email: CustCare-Charlotte@basf.com

Email: edtech_info@basf.com

www.basf.us/dpsolutions