

Joncryl[®] Wax 120

Product Description Joncryl Wax 120 is a paraffin/polyethylene wax emulsion for overprint varnish, industrial coating, and functional packaging coating applications.

Key Features & Benefits

- Water shedding
- Low VOC and coefficient of friction (COF)
- FDA compliance*

Chemical Composition Paraffin/polyethylene wax emulsion

*The full FDA status is available upon request from the contact information provided below

Properties

Typical Properties		
Appearance		tan liquid
Non-volatile	%	34
pH at 25°C		9.0
Viscosity	cps	400
Average particle size	µm	0.08
Density at 25°C	g/cm ³	0.98
Melting Point	°C	56
Freeze-thaw stable		No
Total VOC	% wt	< 0.005

These typical values should not be interpreted as specifications.

Application

Joncryl Wax 120 is a small particle size, very low VOC paraffin/polyethylene wax emulsion designed for water shedding, heat release, and low COF with FDA compliance. It combines the film forming and water shedding characteristics of paraffin wax with the durability and broad compatibility of polyethylene wax.

Joncryl Wax 120 is recommended for applications such as:

- Overprint varnishes for commercial or publication applications
- Functional packaging coating applications
- Interior/exterior general metal coating applications
- Interior/exterior wood coatings for millwork applications

Processing

Joncryl Wax 120 will separate upon aging and must be agitated to uniformity before each use. Failure to follow this procedure will result in unpredictable finished product performance. Inks and coatings containing this product may require “agitate before use” instructions.

Joncryl Wax 120 can result in finished products that are totally impervious to penetration by many conventional adhesive and coating products. Care should be exercised to determine glue-ability and recoat properties of finished formulations and combining this product with other products. Different orders of addition should be evaluated to avoid the possibility of wax kick-out.

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State, and Local health and safety regulations, thorough ventilation of the workplace, good skin care, and wearing of protective goggles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Joncryl Wax 120.

Storage

Please refer to the "Handling and Storage of Polymer Dispersions" brochure.

Important

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE.** Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Joncryl is a registered trademark of BASF Group.

© BASF Corporation, 2019



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico.

For more information on Responsible Care® go to:

U.S.: www.basf.us/responsiblecare_usa

Canada: www.basf.us/responsiblecare_canada

México: www.basf.us/responsiblecare_mexico

BASF Corporation
Dispersions and Resins
11501 Steele Creek Road
Charlotte, North Carolina 28273
Phone: (800) 251 – 0612
Email: CustCare-Charlotte@basf.com
Email: edtech-info@basf.com
www.basf.us/dpsolutions