

Tinuvin[®] 249

Product Description	Tinuvin 249 is a liquid non-basic HALS for coatings. It is designed to meet the high performance and durability requirements of all solvent-based automotive, industrial and decorative coatings where other HALS fail either related to their basicity or for compatibility reasons.
Key Features & Benefits	<ul style="list-style-type: none">- <i>non-basic HALS</i>- <i>low viscosity, solvent-free</i>- <i>does not interact with acidic paint ingredients such as catalyst, biocides or pigments</i>- <i>high thermal stability, excellent color stability during shelf life</i>- <i>broad compatibility in solvent-based systems of different polarity, non-exuding</i>- <i>good long-term performance</i>
Chemical Structure	piperidine derivative

Properties

Typical Properties	CAS No:	proprietary
	Appearance	slightly yellow liquid
	Miscibility	readily miscible with most common organic solvents, immiscible with water

These typical values should not be interpreted as specifications.

Applications

Tinuvin 249 is designed for coatings where traditional HALS fail either related to their basicity (e.g. acid/base interactions) or for compatibility reasons (e.g. exudation).

Fields of application include:

- Automotive OEM and Refinish coatings
- Industrial coatings
- Coil coatings
- Decorative coatings
- Adhesives

For clear-coat applications, Tinuvin 249 needs to be combined with a UV absorber (UVA) such as Tinuvin 400 or Tinuvin 384-2 (automotive finishes) or Tinuvin 1130 (industrial finishes) or Tinuvin 99-2 (decorative finishes).

Binders:

- acid catalyzed thermosetting (acrylic/melamine, PES/melamine...)
- epoxy/carboxy (amine and/or metal catalyzed)
- 2p-PU (polyol/polyester/isocyanate)
- alkyd/acrylic oxidative curing coatings

Recommended Concentrations The concentration of Tinuvin 249 needed depends on the level of pigmentation of the coating. The amount required for optimum performance should be determined in laboratory trials covering a concentration range.

<u>Coating type</u>	<u>by weight on binder solids</u>
Clear coats	1%
Semi-transparent	1 – 2%
Opaque / solid shade	2 – 4%

(concentrations are based on weight percent binder solids)

Safety

General The usual safety precautions when handling chemicals must be observed. These include the measure described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care, and wearing of protective goggles.

Safety Data Sheet All safety information is provided in the Safety Data Sheet for Tinuvin 249.

Storage

Please refer to the “Handling and Storage of Polymer Dispersions” brochure.

Important

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE.** Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Tinuvin is a registered trademark of BASF Group.

© BASF Corporation, 2019



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico.

For more information on Responsible Care® go to:

U.S.: www.basf.us/responsiblecare_usa

Canada: www.basf.us/responsiblecare_canada

México: www.basf.us/responsiblecare_mexico

BASF Corporation
Dispersions and Resins
11501 Steele Creek Road
Charlotte, North Carolina 28273
Phone: (800) 251 – 0612
Email: CustCare-Charlotte@basf.com
Email: edtech-info@basf.com
www.basf.us/dpsolutions